

# SAFETY DATA SHEET - United States

platinum (tetramethyldivinyl-disiloxane) solution in 500 cSt vinyl-terminated poly(dimethylsiloxane) (2% Pt)

## Section 1. Identification

Code: C1218B

GHS product identifier: platinum (tetramethyldivinyl-disiloxane) solution in 500 cSt vinyl-terminated poly(dimethylsiloxane) (2% Pt)

Chemical name: Platinum (tetramethyldivinyl-disiloxane) in 500 cS vinyl-terminated poly(dimethylsiloxane) (2% Pt)

Other means of identification: Not available.

Product type: Liquid.

Relevant identified uses of the substance or mixture and uses advised against: Not applicable.

Supplier's details: Johnson Matthey, 2001 Nolte Drive, West Deptford, NJ 08066 USA

Emergency telephone number (with hours of operation): For Hazardous Materials [or Dangerous Goods] Incident, Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night (collect calls accepted).  
Within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887

## Section 2. Hazards identification


OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture FLAMMABLE LIQUIDS - Category 3  
SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 5%

### GHS label elements

Hazard pictograms



Signal word **Warning**

Hazard statements Flammable liquid and vapor.  
Causes serious eye irritation.  
Causes skin irritation.

### Precautionary statements

**Prevention** Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wash hands thoroughly after handling.

**Response** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified None known.

## Section 3. Composition/information on ingredients

Substance/mixture Mixture

Chemical name Platinum (tetramethyldivinylsiloxane) in 500 cS vinyl-terminated poly(dimethylsiloxane) (2% Pt)

Other means of identification Not available.

### CAS number/other identifiers

CAS number Not applicable.

Product code C1218B

Ingredient name	%	CAS number
Siloxanes and Silicones, di-Me, vinyl group-terminated	90 - 95	68083-19-2
platinum, divinyltetramethylsiloxane complexes	4 - 6	68478-92-2
divinyltetramethylsiloxane	1 - 4	2627-95-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

**Eye contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

**Ingestion** Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** Causes serious eye irritation.
- Inhalation** No known significant effects or critical hazards.
- Skin contact** Causes skin irritation.
- Ingestion** No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** No specific data.
- Skin contact** Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## Section 4. First aid measures

Specific treatments	No specific treatment.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

Suitable extinguishing media Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

Unsuitable extinguishing media Do not use water jet.

Specific hazards arising from the chemical Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
metal oxide/oxides

Special protective actions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark Not available.

Remark Not available.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Siloxanes and Silicones, di-Me, vinyl group-terminated platinum, divinyltetramethyldisiloxane complexes	None. <b>ACGIH TLV (United States, 4/2014).</b> TWA: 1 mg/m <sup>3</sup> , (Platinum) 8 hours. <b>NIOSH REL (United States, 10/2013).</b> TWA: 1 mg/m <sup>3</sup> , (Platinum) 10 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 0.002 mg/m <sup>3</sup> , (Platinum) 8 hours.
divinyltetramethyldisiloxane	None.

**Appropriate engineering controls** Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## Section 8. Exposure controls/personal protection

<b>Body protection</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
<b>Other skin protection</b>	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory protection</b>	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

<b>Physical state</b>	Liquid.	<b>Melting point</b>	Not available.
<b>Color</b>	Clear. Colorless to light yellow. [Light]	<b>Boiling point</b>	Not available.
<b>Odor</b>	Unpleasant. [Slight]	<b>Flash point</b>	Not available.
<b>Odor threshold</b>	Not available.		
<b>Vapor pressure</b>	Not available.		
<b>Vapor density</b>	Not available.	<b>Flammability (solid, gas)</b>	Not available.
<b>Evaporation rate</b>	Not available.	<b>Lower and upper explosive (flammable) limits</b>	Not available.
<b>Relative density</b>	Not available.	<b>Auto-ignition temperature</b>	61.4°C (142.5°F)
<b>pH</b>	Not available.	<b>Decomposition temperature</b>	Not available.
<b>Partition coefficient: n-octanol/water</b>	Not available.	<b>SADT</b>	Not available.
<b>Solubility in water</b>	Not available.	<b>Viscosity</b>	Not available.
<b>Solubility</b>	Insoluble in the following materials: cold water and hot water.		

## Section 10. Stability and reactivity

<b>Reactivity</b>	No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
divinyltetramethyldisiloxane	LD50 Oral	Rat	>5000 mg/kg	-

**Conclusion/Summary** Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
divinyltetramethyldisiloxane	Skin - Edema	Rabbit	0	4 hours 0.5 mL	48 hours
	Skin - Erythema/Eschar	Rabbit	0	4 hours 0.5 mL	48 hours
	Eyes - Mild irritant	Rabbit	-	-	-

**Skin** Not available.

**Eyes** Not available.

**Respiratory** Not available.

## Section 11. Toxicological information

### Sensitization

Not available.

Skin Not available.

Respiratory Not available.

### Mutagenicity

Product/ingredient name	Test	Experiment	Result
divinyltetramethyldisiloxane	EPA 40 CFR 792 and 340 CFR 160	Experiment: In vitro Subject: Bacteria Metabolic activation: with and without	Negative
	476 <i>In vitro</i> Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic Metabolic activation: with and without	Negative
	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal	Negative

Conclusion/Summary Not available.

### Carcinogenicity

Not available.

Conclusion/Summary Not available.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
divinyltetramethyldisiloxane	-	Negative	-	Rat - Male, Female	Oral: >600 mg/kg	-

Conclusion/Summary Not available.

### Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
divinyltetramethyldisiloxane	Positive - Oral	Rat - Female	600 mg/kg per day	up to 52 doses

Conclusion/Summary Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

Information on the likely routes of exposure Not available.

### Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation No known significant effects or critical hazards.

Skin contact Causes skin irritation.

Ingestion No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

## Section 11. Toxicological information

Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

#### Long term exposure

Potential immediate effects	Not available.
Potential delayed effects	Not available.

#### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
divinyltetramethyldisiloxane	Sub-acute NOAEL Inhalation Vapor	Rat - Male, Female	1.9 mg/l	14 days; 6 hours per day

Conclusion/Summary	Not available.
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

Interactive effects	Not available.
Other information	Not available.

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
divinyltetramethyldisiloxane	Acute NOEC >0.12 mg/l Fresh water	Algae - Pseudokirchnerella subcapitata	72 hours
	Acute NOEC >0.1 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute NOEC >0.13 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Conclusion/Summary Not available.

### Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
divinyltetramethyldisiloxane	301D Ready Biodegradability - Closed Bottle Test	0.9 % - 28 days	-	-

Conclusion/Summary Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
divinyltetramethyldisiloxane	-	-	Not readily

### Bioaccumulative potential

## Section 12. Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
divinyltetramethyldisiloxane	-	1290 to 2410	high

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) Not available.

Mobility Not available.

Other adverse effects No known significant effects or critical hazards.




## Section 13. Disposal considerations

**Disposal methods** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**Waste stream** Not available.

**RCRA classification** Not available.

## Section 14. Transport information

	DOT Classification	IMDG	IATA
<b>UN number</b>	UN1993	UN1993	UN1993
<b>UN proper shipping name</b>	Flammable liquids, n.o.s. (platinum, divinyltetramethyldisiloxane complexes, divinyltetramethyldisiloxane, solution)	FLAMMABLE LIQUID, N. O.S. (platinum, divinyltetramethyldisiloxane complexes, divinyltetramethyldisiloxane, solution)	Flammable liquid, n.o.s. (platinum, divinyltetramethyldisiloxane complexes, divinyltetramethyldisiloxane, solution)
<b>Transport hazard class(es) and Packing group</b>	3 III 	3 III 	3 III 
<b>Environmental hazards</b>	No.	No.	No.
<b>Additional information</b>	<p><b>Limited quantity</b> Yes.</p> <p><b>Packaging instruction Passenger aircraft</b> Quantity limitation: 60 L</p> <p><b>Cargo aircraft</b> Quantity limitation: 220 L</p> <p><b>Special provisions</b> B1, B52, IB3, T4, TP1, TP29</p>	<p><b>Emergency schedules (EmS)</b> F-E, _S-E_</p> <p><b>Special provisions</b> 223, 274, 955</p>	<p><b>Passenger and Cargo Aircraft</b>Quantity limitation: 60 L Packaging instructions: 355</p> <p><b>Cargo Aircraft Only</b> Quantity limitation: 220 L Packaging instructions: 366</p> <p><b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 10 L Packaging instructions: Y344</p>



## Section 14. Transport information

			<b>Special provisions</b> A3
--	--	--	---------------------------------

Special precautions for user Avoid exposure. ERG No. 128

Transport in bulk according to Annex II of MARPOL and the IBC Code

Not available.

Proper shipping name Not available.

Ship type Not available.

Pollution category Not available.

## Section 15. Regulatory information

### U.S. Federal regulations

**TSCA 8(a) PAIR:** divinyltetramethylsiloxane

**TSCA 8(a) CDR Exempt/Partial exemption:** Not determined

**United States inventory (TSCA 8b):** All components are listed or exempted.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) Not listed

Clean Air Act Section 602 Class I Substances Not listed

Clean Air Act Section 602 Class II Substances Not listed

DEA List I Chemicals (Precursor Chemicals) Not listed

DEA List II Chemicals (Essential Chemicals) Not listed

### SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ Not applicable.

### SARA 311/312

Classification Fire hazard  
Immediate (acute) health hazard

### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Siloxanes and Silicones, di-Me, vinyl group-terminated	≥90	No.	No.	No.	Yes.	No.
platinum, divinyltetramethylsiloxane complexes	≤10	Yes.	No.	No.	No.	No.
divinyltetramethylsiloxane	≤3	Yes.	No.	No.	Yes.	No.

### State regulations

Massachusetts None of the components are listed.

New York None of the components are listed.

New Jersey None of the components are listed.

Pennsylvania None of the components are listed.

Not available.

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A, B, C, E)

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

## Section 15. Regulatory information

Not listed.

### Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

### International lists

#### National inventory

Australia	All components are listed or exempted.
Canada	All components are listed or exempted.
China	All components are listed or exempted.
Europe	Not determined.
Japan	<b>Japan inventory (ENCS):</b> Not determined. <b>Japan inventory (ISHL):</b> Not determined.
Malaysia	Not determined.
New Zealand	All components are listed or exempted.
Philippines	All components are listed or exempted.
Republic of Korea	All components are listed or exempted.
Taiwan	All components are listed or exempted.
Turkey	Not determined.

## Section 16. Other information

### Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	Expert judgment
SKIN IRRITATION - Category 2	Expert judgment
EYE IRRITATION - Category 2A	Expert judgment

### History

Date of printing	10/01/2017
Date of issue/Date of revision	10/01/2017
Date of previous issue	29/11/2016
Version	3
Prepared by	Not available.

### Key to abbreviations

ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 UN = United Nations

### References

Not available.

🔍 Indicates information that has changed from previously issued version.

## Section 16. Other information

US Label (29 CFR 1910.1200(f)(1))

platinum (tetramethyldivinyl-disiloxane) solution in 500 cSt vinyl-terminated poly(dimethylsiloxane) (2% Pt)



CAS: Not applicable. Code: C1218B

### Warning

Flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation.

Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Wash hands thoroughly after handling. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Store in a well-ventilated place. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 5% Read SDS before using this product. Do not handle until all safety precautions have been read and understood.

Johnson Matthey 2001 Nolte Drive, West Deptford, NJ 08066 USA non-emergencies: +1 856 384 7050; emergencies +1 800 424 9300

### Notice to reader

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is given in good faith, being based on the latest information available to Johnson Matthey PLC and is to the best of Johnson Matthey PLC's knowledge and belief, accurate and reliable at the time of preparation. However, no representation, warranty or guarantee is made as to the accuracy, liability or completeness and Johnson Matthey PLC assumes no responsibility therefore, and disclaims any liability for any loss, damage or injury howsoever arising (including in respect of any claim brought by any third party) incurred using this information. The product is supplied on the condition that the user accepts responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Freedom from patent or any other proprietary rights of any third party must not be assumed.